

Technical specifications



Chassis

- Outside length 910 mm
- Outside width incl. foot pedal 600 mm
- Outside width incl. arm rests 845 mm
- White paint finish
- 2 fixed castors (rigid) \varnothing 100 mm
- 1 swivel castor \varnothing 35 mm
- Optional: foot keypad (2 memory positions, M1/M2)

Upper frame

- 4-part support frame (head, back, seat, leg part)
- Length 1,950 – 2,230 mm
- Width of upholstery 600 mm
- Entry height 550 mm
- Removeable upholstery

	Angle	Dimensions (LxW)
• Head part	-27°/+180°	280 x 420 mm
• Back part	-23°/+85°	710 x 600 mm
• Seat part	-3°/+28°	510 x 600 mm
• Leg part	0°/-75°	490 x 530 mm
• Height adjustment		615 – 890 mm
• Armrests	0°/+180°	455 x 75 mm
• Legroom surgeon		485 – 760 mm
• CPR/flatposition		(height back part) 600 mm

Electrical control

- All components according to IP54
- Hand control with 8 individually programmable memory positions, auto run function, reset button
- Foot keypad (optional)

Electric Drives

- Back, seat, leg part, total up/down

Lifting column

- Max. lifting 275 mm
- Max. load 240 kg
- Motors IPX4 with HAL sensors, to be memorized

Seat part/CPR



Back part/leg part



Height adjustment/legroom



